

DistanceSRF04

Generated by Doxygen 1.7.4

Sun Dec 25 2011 15:26:20

Contents

1	Class Index	1
1.1	Class List	1
2	Class Documentation	1
2.1	DistanceSRF04 Class Reference	1
2.1.1	Constructor & Destructor Documentation	2
2.1.2	Member Function Documentation	2

1 Class Index

1.1 Class List

Here are the classes, structs, unions and interfaces with brief descriptions:

DistanceSRF04	1
----------------------	----------

2 Class Documentation

2.1 DistanceSRF04 Class Reference

Public Member Functions

- [DistanceSRF04 \(\)](#)
DistanceSRF04.cpp - Library for retrieving data from the GP2Y0A21YK IR Distance sensor. For more information: variable declaration, changelog,... see [DistanceSRF04.h](#).
- [void begin \(\)](#)
Begin function to set default pins.
- [void begin \(int echoPin, int trigPin\)](#)
Begin variables.
- [int getDistanceTime \(\)](#)
getDistanceTime(): Returns the time between transmission and echo receive
- [int getDistanceCentimeter \(\)](#)
getDistanceCentimeter(): Returns the distance in centimeters
- [int getDistanceInch \(\)](#)
getDistanceInch(): Returns the distance in inches
- [boolean isCloser \(int threshold\)](#)
isCloser: check whether the distance to the detected object is smaller than a given threshold
- [boolean isFarther \(int threshold\)](#)

- isFarther: check whether the distance to the detected object is smaller than a given threshold*
- void [setAveraging](#) (int avg)
setAveraging(int avg): Sets how many samples have to be averaged in getDistanceCentimeter, default value is 100.

2.1.1 Constructor & Destructor Documentation

2.1.1.1 DistanceSRF04::DistanceSRF04 ()

DistanceSRF04.cpp - Library for retrieving data from the GP2Y0A21YK IR Distance sensor. For more information: variable declaration, changelog,... see [DistanceSRF04.h](#).
Constructor

2.1.2 Member Function Documentation

2.1.2.1 void DistanceSRF04::begin ()

Begin function to set default pins.

2.1.2.2 void DistanceSRF04::begin (int echoPin, int trigPin)

Begin variables.

- int trigPin: pin used to activate the sensor
- int echoPin: pin used to read the reflection

2.1.2.3 int DistanceSRF04::getDistanceCentimeter ()

[getDistanceCentimeter\(\)](#): Returns the distance in centimeters

2.1.2.4 int DistanceSRF04::getDistanceInch ()

[getDistanceInch\(\)](#): Returns the distance in inches

2.1.2.5 int DistanceSRF04::getDistanceTime ()

[getDistanceTime\(\)](#): Returns the time between transmission and echo receive

2.1.2.6 boolean DistanceSRF04::isCloser (int threshold)

isCloser: check whether the distance to the detected object is smaller than a given threshold

2.1.2.7 boolean DistanceSRF04::isFarther (int threshold)

isFarther: check whether the distance to the detected object is smaller than a given threshold

2.1.2.8 void DistanceSRF04::setAveraging (int avg)

setAveraging(int avg): Sets how many samples have to be averaged in getDistance-Centimeter, default value is 100.

The documentation for this class was generated from the following files:

- /home/jeroen/.dropboxstorage/Dropbox/11-arduino/libraries/srf04-library/DistanceSRF04/DistanceSRF04.h
- /home/jeroen/.dropboxstorage/Dropbox/11-arduino/libraries/srf04-library/DistanceSRF04/DistanceSRF04.cpp

Index

begin
 DistanceSRF04, 2

DistanceSRF04, 1
 begin, 2
 DistanceSRF04, 2
 getDistanceCentimeter, 2
 getDistanceInch, 2
 getDistanceTime, 2
 isCloser, 2
 isFarther, 2
 setAveraging, 2

 getDistanceCentimeter
 DistanceSRF04, 2
 getDistanceInch
 DistanceSRF04, 2
 getDistanceTime
 DistanceSRF04, 2

 isCloser
 DistanceSRF04, 2
 isFarther
 DistanceSRF04, 2

 setAveraging
 DistanceSRF04, 2